


PROFILATI A «C»

UNI EN 10219



dimensioni			spessore i n mm				
			1,5	2	2,5	3	3,5
H	B	C	peso kg/m				
25	15	7,5	0,74				
25	25	7,5	0,99				
30	15	7,5	0,81				
30	30	10	1,22	1,60	1,96	2,38	
30	40	10	1,46	1,92	2,36		
35	35	10	1,34	1,72	2,25	2,66	
40	20	10	1,11	1,33			
40	30	15	1,46	1,79			
40	40	10	1,58	2,07			
40	40	15	1,63	2,23	2,75	3,25	
40	50	15	1,87	2,54	3,14	3,44	
45	45	15	1,81	2,34	2,85	3,33	
50	30	15	1,58	2,07			
50	30	20	1,63	2,17	2,56	2,97	
50	40	15	1,81	2,39	2,75	3,21	
50	40	20		2,42	2,95	3,44	
50	50	15		2,58	3,14	3,68	
60	30	15		2,11	2,55	2,97	
60	40	20		2,58	3,15	3,69	
60	50	20		2,89	3,54	4,16	
60	60	20		3,21	3,93	4,63	
70	30	20		2,42	2,95	3,44	
70	40	12		2,50	3,03	3,54	
70	50	12		2,80	3,42	4,01	
80	40	20		2,89	3,59	4,16	
80	50	25		3,36	4,13	4,86	5,56
80	60	15		3,36	4,13	4,86	5,56
80	80	30		4,46	5,50	6,51	7,49
100	50	25		3,68	4,52	5,33	6,10
100	60	30				6,03	6,94
100	70	35				6,74	7,76
100	100	30				7,92	9,13
120	30	12		2,96			
120	60	30		4,46	5,50	6,51	7,49
130	60	30				6,74	7,75
140	50	25				6,27	7,21
140	70	35				7,68	8,87
150	50	25				6,50	7,48
150	70	35				7,93	9,14
180	60	30				7,93	9,14
200	50	25				7,68	8,87